

# ***High-Voltage Lifetime of the ISO72x Family of Digital Isolators***

*Ashish Gokhale and Gaddi Hasse**High-Performance Analog/Interface Products*

## **ABSTRACT**

This application report examines the high-voltage lifetime characteristics of the isolation barrier in the ISO72x family of digital isolators. This provides the user with information regarding the long-term, high-voltage withstand capability of this family of products.

---

### **Contents**

1	Introduction .....	1
2	Insulation Properties and Ratings .....	2
3	ISO72x Device Description .....	2
4	Modeling and Test Methodology .....	3
5	Results .....	4
6	Conclusions .....	5
7	References .....	6

### **List of Figures**

1	Isolation Barrier for ISO72x Family of Products .....	2
2	Test Setup for High-Voltage Lifetime .....	4
3	High-Voltage Lifetime Using TDDDB E Model .....	4
4	High-Voltage Lifetime Based on Best Curve Fit .....	5

### **List of Tables**

1	Typical Data-Sheet Specifications of Insulation Characteristics .....	2
2	High-Voltage Lifetime Predictions Based on TDDDB E-Model .....	5

## **1 Introduction**

Industrial control systems often use digital isolators where downtime costs are high and reliability is a key concern for suppliers of equipment to this market. Data-sheet specifications adequately cover functional and parametric performance of the isolators, including maximum voltage capability of the isolation barrier for single-event, high-voltage transients. However, these specifications do not sufficiently address the behavior of the isolation properties under long-term application of a high voltage.

This application report provides a long-term prediction of the isolation properties of the ISO72x family of digital isolators when operated with a continuous input to output voltage of 560 V at a junction temperature of 150°C.

This report first defines insulation properties and ratings and then describes the ISO72x isolation barrier. It presents the time-dependent dielectric breakdown (TDDDB) model and ISO72x test results.

## 2 Insulation Properties and Ratings

Dielectrics have intrinsic insulation properties determined by their physical and chemical composition, which includes impurities and imperfections (inclusions) that manufacturing may introduce. It is well understood that these inclusions cause the insulation properties to change over time and result in the eventual failure of the dielectric. These changes are accelerated by applying an electric field across the dielectric and/or by increasing its temperature.

Data-sheet specifications for most digital couplers only include initial ratings. For basic insulation applications, most of the commonly available (including ISO72x family) isolated couplers refer to a 4000-V ( $V_{IOTM}$ ) rating. Table 1 refers to typical data-sheet ratings provided by the manufacturer. By itself, this rating does not imply that the product can withstand 4000 V if applied for an indefinite time or at an arbitrarily high temperature. In fact, given only this rating, it is impossible to predict the voltage-withstand characteristics over time of such a product which may be subjected to repeated high-voltage strikes on a factory floor environment, for example.


**Table 1. Typical Data-Sheet Specifications of Insulation Characteristics**

PARAMETER	SYMBOL	MAXIMUM	UNITS
Maximum working insulation voltage	$V_{IORM}$	560	V peak
Transient overvoltage	$V_{IOTM}$	4000	V peak
Input-to-output peak test voltage	$V_{PR}$ , Method b	$1.875 \times V_{IORM}$	V peak
	$V_{PR}$ , Method a	$1.2 \times V_{IORM}$	V peak
Insulation resistance	$R_{IO}$	$> 1E9$	$\Omega$

The other insulation rating that is of concern is the working voltage ( $V_{IORM}$ ), or continuous operating voltage. This voltage rating implies that the product retains its insulation properties over the lifetime of the product if it is operated at this voltage applied between the input and output. Usually, semiconductor products last for a minimum of 10 years.

## 3 ISO72x Device Description

The ISO72x family of products consists of an input and an output semiconductor device separated by a high-impedance isolation barrier designed for the transfer of electrical signals across the barrier. The ISO72x uses capacitive coupling to transmit signals across the barrier while maintaining isolation of the output side with reference to input. The capacitor dielectric is semiconductor-grade silicon dioxide and is the isolation barrier. Figure 1 shows the capacitor is constructed from a top plate consisting of plated copper and a bottom plate made from doped silicon substrate. A BCB (benzocyclobutene) spin-on dielectric passivation over the top plate reinforces the insulation characteristics.



**Figure 1. Isolation Barrier for ISO72x Family of Products**

## 4 Modeling and Test Methodology

### 4.1 The TDDDB E-Model for Dielectric Breakdown

Time-dependent dielectric breakdown (TDDDB) is an important failure mode for dielectric materials like silicon dioxide (SiO<sub>2</sub>). The E-model<sup>(1)</sup> is the most widely accepted and used model for capacitor breakdown and can be applied to all dielectric thicknesses<sup>(2)</sup>. The E-model is not only phenomenological<sup>(3)</sup> but is also backed by a theoretical physical degradation mechanism<sup>(4)</sup>. The E-model is considered as the most conservative of all models in the literature<sup>(5)</sup>. More complex systems, such as the one discussed in this document, may experience multiple failure modes, or degradation mechanisms; each of these modes can be modeled with its respective E-model. The sum of all these dielectric degradation rates would determine the overall time to failure.

A capacitor models the input to output of all isolated devices. The capacitor dielectric thickness and material type can vary from product to product. In the ISO72x family of products, this capacitor is part of the active circuit, as opposed to being part of the parasitic circuit in the case of optocouplers or inductive/magnetic-coupled devices.

The lifetime prediction is accomplished by a series of accelerated-stress TDDDB testing. According to the E-model, the time to failure (TF) relates to the electric field as Equation 1 shows.

$$\ln(\text{TF}) \propto \frac{\Delta H_o}{k_b T} - \gamma E_{ox} \quad (1)$$

where  $\Delta H_o$  is the enthalpy for oxide breakdown (referred to as activation energy),  $E_{ox}$  is the electric field across the isolation barrier, given by the ratio of applied-stress voltage ( $V_S$ ) to thickness of the insulation barrier,  $k_b$  is Boltzmann's constant, and  $\gamma$  is the field acceleration parameter. The data was taken at 150°C, the worst-case operating condition, to avoid the need for temperature corrections. The only TF acceleration was through applying a higher voltage,  $V_S$ . Because  $V_S$  is proportional to  $E_{ox}$ , and temperature acceleration does not have to be accounted for, a simplified model can be used as is shown in Equation 2.

$$\ln(\text{TF}) \propto -MV_s \quad (2)$$

where M (voltage acceleration parameter) is a constant proportional to  $\gamma$ . Thus, using Equation 2, the E-model predicts that the relation is exponential, or, if TF is plotted on the y-axis using a log scale and  $V_S$  on the x-axis using a linear scale, the relation looks linear on such a plot. In this case, M is the slope of this line.

This line is extrapolated to the operating voltage ( $V_{IORM}$ ) for lifetime prediction and will always be overly conservative. This is a result of accelerating the testing by applying voltages much higher than the operating voltage. The higher voltages activate additional dielectric-degradation modes leading to an apparent deviation from the E-model. The additional modes, which may not be active at lower voltages, tend to decrease the slope, which results in a lower projected TF.

- (1) See Reference 1.
- (2) See Reference 2.
- (3) See Reference 3.
- (4) See References 4 and 5.
- (5) See References 6 and 7.

### 4.2 Test Methodology

Normally, semiconductor lifetime is studied at the wafer level. However, due to the voltages involved and to get a more accurate analysis of the failure modes of the product, packaged units were used for testing in this application report. Through-hole, dual-in-line packages (DIP) generated artifact-free data in the test setup; therefore, DIP units generated the majority of the data points. Small-outline integrated circuit (SOIC) and DIP devices were tested and analyzed to confirm that the same failure modes were activated. Figure 2 shows the test setup for a device under test (DUT).




Figure 2. Test Setup for High-Voltage Lifetime

The basic methodology was to apply a stress voltage from the input to the output of the DUT in a two-terminal configuration using a high-voltage source, while maintaining the still-air, ambient-air temperature at 150°C. The start of the test activated a timer; this timer stopped when the current in the circuit exceeded 1 mA, which meant that the dielectric had failed. The TF was noted for each applied test voltage. DUTs were tested independently of each other (one DUT per test) at each test voltage to get statistically valid results.

## 5 Results

### 5.1 TDDB E-Model Predictions

The raw data was statistically analyzed using a linearized Weibull<sup>(6)</sup> plot to determine the worst-case TF; this was extrapolated down to 10-ppm level at each test voltage. The extrapolated TF (10 ppm) is plotted against test voltage in Figure 3.




Figure 3. High-Voltage Lifetime Using TDDB E Model

<sup>(6)</sup> See Reference 12. Weibull plots are better suited for analyzing data such as capacitor breakdown.


Table 2 summarizes the lifetime predictions at different values of  $V_{IORM}$  ( $V_{peak}$ ) using the TDDDB E-model illustrated in Figure 3.

**Table 2. High-Voltage Lifetime Predictions Based on TDDDB E-Model**

$V_{IORM}$ , $V_{peak}$	Lifetime per TDDDB E-Model ( in Years)
200	85
400	46
<b>560</b>	<b>28</b>
700	18
800	13

## 5.2 Model Comparison

Unlike the use of the E-model, competitors often use an arbitrary fit to their data, that is not based on any physical dielectric degradation models. An example is a power fit shown in Figure 4. The same data used in Figure 3 was plotted here and a best-fit trend-line was generated using a power curve as shown in Figure 4. As can be seen, significantly longer lifetimes can be expected using such an approach. Published competitor data (also at 10-ppm levels) for inductive coupled devices are included for comparison. The competitor data was published using a time scale in years; therefore, in Figure 4, those units were converted from years to seconds for comparison. TI's preference for using the TDDDB E-model is based on the fact that this model is conservative and should result in high-confidence predictions compared to any other models or a best data fit methodology.



**Figure 4. High-Voltage Lifetime Based on Best Curve Fit**

## 6 Conclusions

The ISO72x family of products can be safely operated for over 25 years at an operating voltage of 560 V. Results also show that the isolation barrier is robust and can withstand multiple instances of high-voltage spikes of up to 4000  $V_{peak}$  or 2828  $V_{rms}$ , as specified by the  $V_{IOTM}$  rating

## 7 References

1. *Comparison of E and 1/E TDDDB Models for SiO<sub>2</sub> Under Long Term/Low Field Test Conditions*, Joe McPherson, Vijay Reddy, Kaustav Banerjee, and Huy Le, Texas Instruments and University of California at Berkeley, IEDM 98-171-174
2. *Reliability Analysis Method for Low-k Interconnect Dielectrics Breakdown in Integrated Circuits*, G.S. Haase, E.T. Ogawa, and Joe McPherson, Journal of Applied Physics 98, 34503-34514 (2005)
3. A. Berman, *Proc. International Reliability Physics Symposium*, IEEE 1981, page 204
4. Joe McPherson and D. Baglee, *Proc. International Reliability Physics Symposium*, IEEE 1985, page 1
5. Joe McPherson and H.C. Mogul, Journal of Applied Physics 84, 1513 (1984)
6. *A Unified Gate Oxide Reliability Model*, Chenming Hu and Qiang Lu, University of California, Berkeley; IEDM 99-445-448
7. *A Consistent Model for Time Dependent Dielectric Breakdown in Ultrathin Silicon Dioxides*, Kenji Okada and Kenji Yoneda, Matsushita Electronics Corporation; IEEE 99CH36296. 37th Annual International Reliability Physics Symposium, San Diego, CA 1999
8. *HCPL-0721 Data Sheet*, Avago Technologies
9. *iCoupler Isolation Technology: Eliminate Those Optocoupler Headaches!*, Analog Devices
10. *ADuM1100 Datasheet Revision E*, Analog Devices
11. *ISO72x data sheet*, ([SLLS629](#)) Texas Instruments
12. *Probability and Statistics for Engineers, Third Edition*, Irwin Miller, John E. Freund, Prentice Hall ISBN 0-13-711938-0

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

<b>Products</b>		<b>Applications</b>	
Amplifiers	<a href="http://amplifier.ti.com">amplifier.ti.com</a>	Audio	<a href="http://www.ti.com/audio">www.ti.com/audio</a>
Data Converters	<a href="http://dataconverter.ti.com">dataconverter.ti.com</a>	Automotive	<a href="http://www.ti.com/automotive">www.ti.com/automotive</a>
DSP	<a href="http://dsp.ti.com">dsp.ti.com</a>	Broadband	<a href="http://www.ti.com/broadband">www.ti.com/broadband</a>
Interface	<a href="http://interface.ti.com">interface.ti.com</a>	Digital Control	<a href="http://www.ti.com/digitalcontrol">www.ti.com/digitalcontrol</a>
Logic	<a href="http://logic.ti.com">logic.ti.com</a>	Military	<a href="http://www.ti.com/military">www.ti.com/military</a>
Power Mgmt	<a href="http://power.ti.com">power.ti.com</a>	Optical Networking	<a href="http://www.ti.com/opticalnetwork">www.ti.com/opticalnetwork</a>
Microcontrollers	<a href="http://microcontroller.ti.com">microcontroller.ti.com</a>	Security	<a href="http://www.ti.com/security">www.ti.com/security</a>
		Telephony	<a href="http://www.ti.com/telephony">www.ti.com/telephony</a>
		Video & Imaging	<a href="http://www.ti.com/video">www.ti.com/video</a>
		Wireless	<a href="http://www.ti.com/wireless">www.ti.com/wireless</a>

Mailing Address: Texas Instruments  
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2006, Texas Instruments Incorporated